Cordless IQV™ Tools and Accessories | Other tools

C1101EU-K2 Kit- 2BAT. 2.0 Ah & charger, CCN:47559320001

- Includes 6 variable blades
- Application include but not limited to sheet metal (up to 1.5mm), body panels, plastic and composite cutting
- r2.0 battery with fuel gauge

C1101 Tool only - 12 V
CCN:47559320001

G1811EU-K2 Kit- 2BAT. 2.0 Ah & charger, CCN:47559180001

- Includes 3x 60grit and 3x80grit belts
- Application include but not limited to sanding metal, plastic, fiberglass, glass;removing spor welds, rust, deburring and finishing surfaces
- r2.0 battery with fuel gauge

G1811 Tool only - 12 V
CCN:47559185001

G1621EU-K2, 2 BAT. Kit CCN: 47540140001
12 V Sander/Polisher, Charger, 2XBL1203 (2.0 Ah) Li-Ion Batteries

- Cordless Sander/Polisher
- 2" (50 mm) and 3" (75 mm) pads
- 2-speed gearbox, quick change spindle-lock and variable-speed for use on multiple surfaces
- Low noise level

G1621
Tool only - 12 V
CCN: 47542795001

Ref.	CCN	Battery	V	rpm	HH:MM	Lumens	kg	mm	dB(A)	m/s²/K(1)
LUB5130	47503006	BL2022, BL2012	20	–	–	–	3.70	490	66.0	2.5
G1621	47542795001	BL1203	12	2,200	0:20	–	1.30	144	67.0	3.0/0.8
L5110	48489561	BL2012	20	–	12:50	180	0.86	236	–	–
L1110	47500109001	BL1203	12	–	6:50	180	0.58	217	–	–
C1101	47559320001	BL1203	12	3,300	0:20	-	2.14	298	77	17.9/7.8
G1811	47559185001	BL1203	12	7,000	0.20	-	2.23	134	70	1.9/0.6

L5110 Tool only - 20 V
CCN: 48489561

- Ultra-bright white LED casts 180 lumens
- Compatible with all IQV20 batteries
- Multi-position head, standing base and hang hook allow for lighting from above or below at any angle
- Run time: 12.5 hours (BL2012)/;15 hours (BL2010)/22 hours (BL2022)

L1110 Tool only - 12 V
CCN: 47500109001

- Ultra-bright white LED casts 180 lumens
- Multi-position head, standing base allow for lighting from below at any angle
- Run time: 6 hours (BL2012)

LUB5130-K12-EU Kit
CCN: 47503151001
20 V Grease Gun, Charger 12/20 V,
1 BL2012 (2.5 Ah) Li-Ion Battery & Case

- Cordless Grease Gun
- Pressure 431 bar (6,250 psi)
- Flowrate 75 g/min
- Grease capacity 400 g
- 3 way loading: bulk, cartridge and manual
- Flexible hose 762 mm

LUB5130 Tool only - 20 V
CCN: 47503006

(1) Weight to include tool + battery weights
(2) ISO28927 – 3-axis measurement: vibration level/measurement uncertainty.