

# 2175MAX-6

# 1" Impactool™ with extended anvil



The 2175MAX-6 Impactool delivers exceptional power and rugged durability in a convenient, easy-to-use package. It is the perfect tool for the most demanding applications, such as truck and bus service, construction and agricultural equipment maintenance, tire changing, as well as the MRO market.

- 2715 Nm (2000 ft-lb) of maximum torque.
- The Ingersoll Rand impact mechanism with proprietary advanced metallurgy provides the ultimate in durability and reliability
- Ingersoll Rand TwinHammer impact mechanism is the strongest, most durable and longest life mechanism in the industry
- Powerful 6-vane motor delivers superior performance.
- Ergonomic handle design provides a secure and comfortable
- Ergonomic auxiliary handle provides excellent maneuverability.
- Feather-touch trigger allows precise delivery of power and
- 2-position power regulator and forward/reverse control.
- 360° swivel inlet helps eliminating twisted hoses.
- FREE two-year limited warranty without tool registration.

# Specifications at 6.2 bar (90 psi)

Part Number	2175MAX-6
Ordering number	2175MAX-6
Drive size (square)	1 in
Drive length	6 in / 150 mm
Torque settings (forward / reverse)	2/2
Other available versions:	
- standard length anvil	2175MAX

### PERFORMANCE

2000 ft-lb / 2715 Nm Maximum torque Recommended fastener size 1-1/4 in / M32 4500 rpm Free speed Impacts per minute 740

# AIR SYSTEM

Air Inlet (NPT) 1/2 in 3/8 in / 13 mm Minimum hose size 14.2 CFM / 402 L/min Average air consumption 56.7 CFM / 1606 L/min Air consumption at load

### **NOISE & VIBRATION**

Impacting sound pressure / power (ISO15744) 101.5 / 112.5 dB(A) Free speed sound pressure / power (ISO15744) 103.6 / 114.6 dB(A) Vibration level / measurement uncertainty (ISO28927) 11.2 / 3.4 m/s<sup>2</sup>

#### WEIGHT & DIMENSIONS

20 lb / 9.1 kg Tool weight 16 in / 406 mm Tool length Shipping weight 25.4 lb / 11.5 kg Shipping dimensions (L x W x H) 527x 362 x 159 mm UPC / EAN code 6 63023 13966 1 Made in PRC Oriain





# 2175MAX-6

# **ACCESSORIES**



SK8M4LN

SK8M4LN

1" Impact socket set (4 pcs) (27, 30, 32 and 33 mm)



#### Impact sockets

For the complete range, see our accessory catalogue.



#### Socket retainer rings

For the complete range, see our accessory catalogue.



327-EU 01343771

10 mm high-speed tire buffer



327LS 01371699

7/16" tire buffer



2175-K285

47646977001

Exhaust connection for Pipe-away



2175-K674

47648454001

External muffler kit



#### 33304

91488205

Hose whip, 1/2" NPT, 13 mm inside diameter, 30 cm (1 ft)



#### IB11NMC4

25014036

IBN/IBS Series nipple, 1/2" male thread, 11 mm bore (ISO6150B / MIL-



## **Quick Release Couplings**

For the complete range, see our accessory catalogue.



## **RH-12**

92536051

PVC hose, 13 mm inside diameter, 30 m



## CO-1518

56753122

Hose clamps, 15-18 mm outside diameter, 100 pcs



#### Filters, regulators, lubricators

For the complete range, see our accessory catalogue.



#### 105-LBK1

04616090

Lubricant kit for Impactools™ with metal housing



## 10**Z**4

03875671

Oil, Class 1, no. 10, 0.12 L



#### 105-4T-6

04618930

Grease for Impactools hammer mechanism (6 tubes)



#### Lubricants

For the complete range, see our accessory catalogue.



2175MAX-TK1

47629423001

Motor service kit



# ingersollrandproducts.com

Nothing contained on these pages is intended to extend any warrantly or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.