

# 1/4" and 3/8" Air Impacttools™

## 2115PTiMAX - 3/8" pin type 2115QTiMAX - 3/8" ring type



- 407 Nm (300 ft-lb).
- Only 1.13 kg and 151mm.
- Twin-hammer impact mechanism.
- Titanium hammer case and composite housing.
- 4-position power regulator.
- 1-hand forward and reverse switch.

Accessories: **2115-BOOT** (CPN: 45505351), protective tool boot.

## 2115XP - 3/8"

- 370 Nm (273 ft-lb).
- Only 1.13 kg and 151 mm.
- Twin-hammer impact mechanism.
- Aluminum hammer case and composite housing.
- 4-position power regulator.
- 1-hand forward and reverse switch.

Accessories: **2115-BOOT** (CPN: 45505351), protective tool boot.

**NEW**

## 2102XP - 3/8" 2101XP - 1/4"

- 68 Nm (50 ft-lb).
- Only 0.6 kg and 165 mm.
- Swinging-hammer impact mechanism.
- Composite housing.
- 1-hand forward and reverse switch.

**NEW**

## 216B - 3/8"

- 271 Nm (200 ft-lb).
- Only 1.27 kg.
- Ball & cam impact mechanism.
- Power regulator.

## 212 - 3/8"

- 244 Nm (180 ft-lb).
- Only 1.31 kg.
- Jumbo-hammer impact mechanism.
- 5-position power regulator.

Accessories: **212-BOOT** (CPN: 45505344), protective tool boot.

## 211 - 3/8"

- 204 Nm (150 ft-lb).
- Only 1.09 kg.
- Jumbo-hammer impact mechanism.
- 5-position power regulator.

## LA158 - 3/8"

- 136 Nm (100 ft-lb).
- Only 1.25 kg and 137 mm.
- Swinging-Hammer impact mechanism.
- Power regulator.



## 2015MAX - 3/8"

- 244 Nm (180 ft-lb).
- Only 1.54 kg.
- Jumbo-hammer impact mechanism.
- Composite housing.
- 2-position power regulator.

*The power of an impact with the reach of a ratchet!*

## Service Kits



	A	B
2115PTiMAX	45585189	45585932
2115QTiMAX	45585189	45585932
2115XP	45585189	45585932
2015MAX	47100474	47100359
212	03866522	—
211	03866449	—
LA158	49827108	49827090

### Specifications at 6.2 bar (90 psi)

	CPN	Nm	Max Nm	1 min. rpm	1 min.	kg	mm	AIR NPTF	AIR mm	L/s	Max L/s	dB(A)	m/s <sup>2</sup> / K(1)
<b>3/8" <input type="checkbox"/></b>													
2115PTiMAX	45587540	34-312	407	15 000	1 500	1.13	151	1/4"	10	1.9	8.0	93.2	7.5 / 1.8
2115QTiMAX	45587326	34-312	407	15 000	1 500	1.13	151	1/4"	10	1.9	8.0	93.2	7.5 / 1.8
2115XP	45632130	34-285	370	15 000	1 500	1.13	151	1/4"	10	1.9	8.0	94.0	7.5 / 1.8
216B	46806600	20-217	271	8 500	1 600	1.27	196	1/4"	10	1.4	9.0	90.0	5.2 / 1.0
2015MAX	45533775	61-190	244	7 100	2 100	1.54	332	1/4"	10	1.6	9.0	96.6	17.4 / 3.0
212	01343151	27-170	244	10 000	1 500	1.31	152	1/4"	10	1.2	5.2	97.5	6.5 / 1.0
211	01343235	27-170	204	10 000	1 500	1.09	168	1/4"	10	1.2	5.2	104.0	5.9 / 1.6
LA158	49825870	7-100	136	10 000	1 400	1.25	137	1/4"	10	1.9	7.5	88.4	3.3 / 1.1
2102XP	16619686	34-54	68	11 000	1 250	0.63	165	1/4"	10	0.8	8.6	85.8	4.4 / 0.8
<b>1/4" <input type="checkbox"/></b>													
2101XP	16599466	34-54	68	11 000	1 250	0.63	165	1/4"	10	0.8	8.6	85.8	4.4 / 0.8

(1) ISO28927 – 3-axis measurement: vibration level / measurement uncertainty.